

Wrenches and other spare parts

Insert	Part Number	Dimension (mm)						Angle (°)		Remarks
		A	B	C	D	E	F	α	θ	
	DT -7	44.0	16.0	-	114	-	T7	-	-	Torx
	DTM -6	39.0	17.0	-	113	-	T6	-	-	Top of Torx is magnetized
	-8	70.0	24.0	-	150	-	T8	-	-	
	DTPM -8	70.0	24.0	-	150	-	8IP	-	-	⊙⊙IP shows Torx Plus Top of Torx is magnetized
	FH -2	42.0	20.0	-	73	2.0	-	-	-	Hexagon
	-2.5	42.0	20.0	-	73	2.5	-	-	-	
	FT -5									Torx
	-6	30.0	20.0	-	65	-	T6	-	-	
	-7	34.0	15.0	-	62	-	T7	-	-	
	-8	35.0	20.0	-	74	-	T8	-	-	
	-10	40.0	20.0	-	74	-	T10	-	-	
	FT -15	43.0	25.0	10	80	-	T15	-	-	Torx
	LTW -8SS	45.0	6.0	-	-	-	T8	-	-	Torx
	-10S	65.0	10.0	-	-	-	T10	-	-	
	-10SS	50.0	7.0	-	-	-	T10	-	-	
	-15S	65.0	10.0	-	-	-	T15	-	-	
	-20	57.0	20.0	-	-	-	T20	-	-	
	LW -1.5	45.0	14.0	-	-	1.5	-	-	-	Hexagon
	-2	50.0	16.0	-	-	2.0	-	-	-	
	-3	63.0	20.0	-	-	3.0	-	-	-	
	-4	70.0	25.0	-	-	4.0	-	-	-	
	LTK -5	70.0	30.0	-	-	-	-	-	-	
	PC -1	60.0	8.5	-	-	-	-	-	-	Punch
	-2	65.0	10.0	-	-	-	-	-	-	

GRADES	A
INSERTS	B
CBN & PCD	C
TURNING	E
BORING	F
GRINDING	G
CUT-OFF	H
THREADING	J
SOLID END MILLS	L
MILLING	M
SPARE PARTS	P
TECHNICAL	R
INDEX	T