


**Screws / Bolts**

Drawing	Part Number	Dimension (mm)						Angle (°)		Torque (N • m)	Notes
		A	B	C	D	E	F	α	θ		
	HS 3X4P	M3X0.5	3.9	-	-	1.5	-	-	-	1.0	HS4X4P and HS6X4P Have a Flat Edge  Clamp Screw Equivalent to JIS B-1177
	3X4		4.0								
	3X8		8.0								
	3X12		12.0								
	3X16		16.0								
	HS 4X4P	M4X0.7	3.9	-	-	2.0	-	-	-	2.0	
	4X4		4.0								
	5X5		5.0								
	HS 6X4P	M6X0.75	3.9	-	-	3.0	-	-	-	4.0	
	6X6	6.0									
	6X8T	M6X1.0	8.0								
	6X14		14.0								
	6X22		22.0								
	HS 8X10	M8X1.25	10.0	-	-	4.0	-	-	-	-	
	8X12		12.0								
	HS 10X10	M10X1.5	10.0	-	-	5.0	-	-	-	-	
	10X16		16.0								
	HS 12X12	M12X1.75	12.0	-	-	6.0	-	-	-	-	
12X16	16.0										
12X18	18.0										
12X20	20.0										
12X25	25.0										
12X30	30.0										
HS 16X12	M16X2.0	12.0	-	-	8.0	-	-	-	-		
16X18		18.0									
16X20		20.0									
	HSB 4X8%	M4X0.7	8.0	R2.0	-	2.0	-	-	-	2.0	R Shows Right-hand Thread L Shows Left-hand Thread
	LS -03	M5X0.8	10.0	M5X0.8	-	2.0	-	-	-	2.0	N : Silver Coated
	-03S		12.2			2.5				3.0	
	LS -03N	M5X0.8	9.7	M5X0.8	-	2.0	-	-	-	2.0	
	-03SN		12.0			2.5				3.0	
	LS -05	M5X0.8	15.5	M5X0.8	-	2.0	2.0	-	-	2.0	
	LS -1	M6X1.0	17.0	6.0	-	2.5	2.5	-	-	3.0	N : Silver Coated
	-1N		14.2								
	-1S		21.0								
	-1SN		21.0								
	LS -2	M8X1.0	20.0	8.0	-	3.0	3.0	-	-	4.0	
	-2N		22.0								
	-3		24.0								
	-4		24.0								
LS -1P	M6X1.0	16.5	6.0	-	10IP	10IP	-	-	2.0	OOIP Shows Torx Plus	
-2P	M8X1.0	18.2	8.0	-	15IP	15IP	-	-	3.5		
-3P		21.8									
	LS -11	M6X1.0	9.5	-	-	3.0	-	-	-	-	
	-15		12.5								
	M 3X8	M3X0.5	8.0	5.5	2.0	-	-	-	-	-	Flat Fillister Head Screw Equivalent to JIS B-1101
	3X12		12.0								
	4X10	M4X0.7	10.0	7.0	2.6						

**Reference**

Torx and Torx Plus have different cross-sections.



Torx

Torx Plus