

**Screws / Bolts**

Drawing	Part Number	Dimension (mm)						Angle (°)		Torque (N • m)	Notes	
		A	B	C	D	E	F	α	θ			
	<b>SB -4070TRW</b>	M4X0.7	6.7	5.5			T8		60°	1.2	R Shows Right-hand Thread	
	<b>-4590TRWN</b>	M4.5X0.75	9.3	5.6			T10		57°	2.0		
	<b>SC -30067</b>	M3X0.35	6.7	4.4			T8		60°	1.2		
	<b>-35085</b>	M3.5X0.35	8.5	5.7			T10			2.0		
	<b>-40100</b>	M4X0.5	10.0	6.0			T15			3.5		
	<b>-50130</b>	M5X0.5	13.0	6.6			T20		40°	4.5		
	<b>-60160</b>	M6X0.75	16.0	8.0			T25			6.0		
	<b>-60210</b>	M6X0.75	21.0	9.6			T30			8.0		
	<b>SCR -01</b>	M2.5X0.45	6.6	3.6			T7		60°	0.8		
	<b>-03</b>	M3X0.5	8.4	4.6			T9			1.6		
	<b>-04</b>	M2.5X0.45	4.6	3.6			T7			0.8		
	<b>-05</b>	M2.5X0.45	4.6	3.6			T7			0.8		
	<b>-16</b>	M3.5X0.6	6.9	5.0			T10					2.0
	<b>-30</b>		8.9									
	<b>SE -3070TRP</b>	M3X0.5	7.0	4.3			9IP		43°	1.7	OOIP Shows Torx Plus	
	<b>-40050TRN</b>		5.0									
	<b>-40055TR</b>		5.5									
	<b>-40068TR</b>	M4X0.7	6.8	5.0			T15		44°	3.5		
	<b>-40080TR</b>		8.0									
	<b>-40090TR</b>		9.0									
	<b>-40100TR</b>		10.0									
	<b>SE -40120TR</b>	M4X0.7	12.0	5.6			T15		60°	3.5		
	<b>-50125TR</b>	M5X0.8	12.5	6.8			T20			4.5		
	<b>SH -50150TR</b>	M5X0.8	15.1	7.3	3.1		T20			4.5		
	<b>SP 3X4</b>	M3X0.5	4.0	4.0					90°	-	With Additional Machining Below the Fillister Head	
	<b>3X6</b>		6.0									
	<b>3X8</b>		8.0	6.0								
	<b>3X10</b>		10.0									
	<b>SP 4X9</b>	M4X0.7	9.0	5.6		2.0			90°	-		
	<b>SP 8X35</b>	M8X1.25	35.0	11.0	4.4	5.0			90°	-		
	<b>SPW -6045</b>	M6X0.75	9.0	7.5	M4.5X0.75	4.5					A Shows External D Shows Internal External and Internal Threads are Both Right-hand Threads	
	<b>-7050</b>	M7X0.75	9.0	8.8	M5X0.8	5.0						
	<b>SS -4N</b>	M5.5X0.5	8.5	6.6	M4X0.7	4.0						
	<b>SV -60136R</b>	M6X1.0	13.6	6.3		4.0			6°	-	Hexagon Socket	
	<b>-60136TR</b>						T20			4.5	Torx	
	<b>TH 8X15</b>	M8X1.25	20.0	8.5		4.0						
	<b>W 6X17</b>	M6X1.0	17.0				T20			4.5		
	<b>6X18N</b>		18.0				T15			3.5		
	<b>8X16</b>		M8X1.0	16.0				T25		6.0		
	<b>W 6X18</b>	M6X1.0	17.5				3.0					
	<b>6X20</b>	M6X1.0	20.5									
	<b>8X18</b>	M8X1.25	18.0									
	<b>*8X21</b>	M8X1.0	21.0									4.0
	<b>XNS 610</b>	3/8-24UNF	1.250*	0.500*		0.188*					Differential Screw	

\* No Socket on Right-hand Thread Side