



для заказа - kyocera@kyocera-tools.ru

Dynamic Bars / EZ Bar PLUS (metric)

Application	Shape	Boring Bar Type	Shank Type Max. Overhang Length L/D	Coolant Hole Yes	Coolant Hole No	Min. Bore Dia. ØA (mm) 5	6	7	8	10	12	13	14	16	18	20	22	23	25	26	27	30	31	32	34	40	50	Toolholder / Sleeve Ref. Page
Boring / Internal Facing		A...SCLC-AE	Excellent L/D = ~5.5	●						●	●		●		●		●				●							F38
		S...SCLC-AE	Excellent L/D = ~5.5		○	●	●	●	●																			
		S...SCLC-A	Steel L/D = ~4.0		○					●	●		●		●		●				●							
		C...SCLC-A	Carbide L/D = ~7.0		○	●	●	●	●																			
		E...SCLC-A	Carbide L/D = ~7.0	●						●	●		●		●		●				●							
		A...SCLP-AE	Excellent L/D = ~5.5	●							●		●	●	●		●				●							
		S...SCLP-A	Steel L/D = ~4.0		○						●		●	●	●		●				●							
		E...SCLP-A	Carbide L/D = ~7.0	●							●		●	●	●		●				●							
	EZ Bar PLUS 	S...SCLC-EZ	Steel L/D = ~3.0		○	●		●																			F20
		C...SCLC-EZ	Carbide L/D = ~5.0		○	●		●																				
		A...STLP-AE	Excellent L/D = ~5.5	●						●	●		●	●	●		●		●		●							F52
		S...STLB-AE			○				●																			
		S...STLB(P)-A	Steel L/D = ~4.0		○				●	●	●		●	●	●		●				●							
		E...STLP-A	Carbide L/D = ~7.0	●						●	●		●	●	●		●		●		●							
		C...STLB-A			○				●																			
		A...STLC-AE	Excellent L/D = ~5.5	●						●	●		●		●		●											F51
		S...STLC-A	Steel L/D = ~4.0		○					●	●		●		●		●											
Boring		S...SWUB-AE	Excellent L/D = ~5.5		○		●	●	●																			F66
		A...SWUB(P)-AE	Excellent L/D = ~5.5	●						●	●		●		●		●											
		S...SWUB(P)-A	Steel L/D = ~4.0		○		●	●	●	●	●		●		●		●											
		C...SWUB-A	Carbide L/D = ~7.0		○		●	●	●																			
		E...SWUB(P)-A	Carbide L/D = ~7.0	●						●	●		●		●		●											

kyocera@kyocera-tools.ru
www.kyocera-tools.ru