


для заказа - kyocera@kyocera-tools.ru

GBA Inserts (Inch)

Part Number	A	T	Ød
	(in)		
GBA32_	0.375	0.125	0.173
GBA43_	0.500	0.187	0.217
GBA43R480	0.500	0.197	0.217

P	Carbon Steel / Alloy Steel	●	◔
M	Stainless Steel		●
K	Cast Iron		
N	Non-ferrous Metals		
S	Titanium Alloy		●
H	Hard materials (≤40HRC)		●
	Hard materials (≥40HRC)		

Classification of Usage
- ◔ : Light Interruption / 1st Choice
- ◷ : Light Interruption / 2nd Choice
- ● : Continuous / 1st Choice
- ○ : Continuous / 2nd Choice

Insert (Right-handed Insert Shown)	Part Number	Previous Part Number	Unit	Dimensions (in) W	B	rε	MEGACOAT Cermet PV7040	MEGA COAT PR1215	Applicable Toolholders	Ref. Page for Toolholder
 Molded Chipbreaker MY Chipbreaker 	GBA43R 078MYN	-	inch	0.078	0.138	0.008		●	KGBAR…4-15 KGBAR…22-15 KGBASR…4-15 KGBASR…22-15	G11 G62 (Internal)
	GBA43R 094MYN	-		0.094	0.157	0.012		●	KGBAR…4-25 KGBAR…22-25 KGBAR…4-25T KGBAR…22-25T5 KGBASR…4-25 KGBASR…22-25 KGBASR…22-25T5	
	GBA43R 125MYN	-		0.125	0.157	0.012		●		
	GBA43R 156MYN	-		0.156	0.197	0.016		●	KGBAR…4-35 KGBAR…22-35 KGBASR…4-35 KGBASR…22-35	
 Full-R (Round) 	GBA32R 031R	-	inch	0.062	0.079	0.031		●	KGBAR…-3 KGBAR…-16 KGBASR…-3 KGBASR…-16	
	047R	-		0.094	0.098	0.047		●		
	GBA43R 031R	-		0.062	0.138	0.031		●	KGBAR…4-15 KGBAR…22-15 KGBASR…4-15 KGBASR…22-15	
	047R	-		0.094	0.157	0.047		●	KGBAR…4-25 KGBAR…22-25 KGBAR…4-25T KGBAR…22-25T5 KGBASR…4-25 KGBASR…22-25 KGBASR…22-25T5	
	062R	-		0.125	0.157	0.062		●		
	078R	-		0.156	0.197	0.078		●	KGBAR…4-35 KGBAR…22-35 KGBASR…4-35 KGBASR…22-35	
	094R	-		0.188	0.197	0.094		●		

• Dimension B shows available grooving depth

Recommended Cutting Conditions ➔ G123

Inserts are sold in 5 piece boxes.

● : U.S. Stock Standard
○ : World Express (Shipping: 7-10 Business Days)

kyocera@kyocera-tools.ru
www.kyocera-tools.ru