для заказа - kyocera@kyocera-tools.ru




Applicable Inserts

(in)

Part Number	A	L	H	Ød
GE□...-A	0.263	0.256	0.102	0.098
GER...-AR				
GE□...-B	0.333	0.323	0.125	0.106
GER...-BR				

		Cermet	MEGACOAT	PVD Coated Carbide	Carbide	
		TN6020	PR1225	PR1025	GW15	KW10
P	Carbon Steel / Alloy Steel		●	◔		
M	Stainless Steel		●	◔		
K	Cast Iron					◔
N	Non-ferrous Metals					●
S	Titanium Alloy					●
H	Hard materials (≤40HRC)		●	○		

Classification of Usage
● : Light Interruption / 1st Choice
◔ : Light Interruption / 2nd Choice
● : Continuous / 1st Choice
○ : Continuous / 2nd Choice

Insert (Right-handed Insert Shown)	Part Number	Unit	Dimensions (in) W inch	W mm	B	C	rε	Applicable Toolholders	Ref. Page for Toolholder
 2-Edge 	GE□ 031-002A	inch	0.031	0.79	0.037	0.071	0.002	SIGE□...A-EH SIGE□...A-WH	G55 G56
	041-002A		0.041	1.04	0.059	0.071	0.002		
	047-002A		0.047	1.19	0.059	0.071	0.002		
	058-002A		0.058	1.47	0.059	0.071	0.002		
	062-004A		0.062	1.57	0.059	0.071	0.004		
	072-004A		0.072	1.83	0.059	0.071	0.004		
	078-004A		0.078	1.98	0.059	0.071	0.004		
	GE□ 100-005A	inch	0.039	1.00	0.059	0.071	0.002	SIGE□...A-EH SIGE□...A-WH	G55 G56
	120-005A		0.047	1.20	0.059	0.071	0.002		
	125-005A		0.049	1.25	0.059	0.071	0.002		
	150-010A		0.059	1.50	0.059	0.071	0.004		
	200-010A		0.079	2.00	0.059	0.071	0.004		
	GE□ 031-002B	inch	0.031	0.79	0.044	0.102	0.002	SIGE□...B-EH SIGE□...B-WH SIGER...B-WH-90	G55 G56 G57
	041-002B		0.041	1.04	0.087	0.102	0.002		
	047-002B		0.047	1.19	0.087	0.102	0.002		
	058-002B		0.058	1.47	0.087	0.102	0.002		
	062-004B		0.062	1.57	0.087	0.102	0.004		
	072-004B		0.072	1.83	0.087	0.102	0.004		
	078-004B		0.078	1.98	0.087	0.102	0.004		
	088-004B		0.088	2.24	0.087	0.102	0.004		
	094-004B		0.094	2.39	0.087	0.102	0.004		
	097-004B		0.097	2.46	0.087	0.102	0.004		
	105-008B		0.105	2.67	0.087	0.102	0.008		
	110-008B		0.110	2.79	0.087	0.102	0.008		
	122-008B		0.122	3.10	0.087	0.102	0.008		
	GE□ 100-005B	inch	0.039	1.00	0.087	0.102	0.002	SIGE□...B-EH SIGE□...B-WH SIGER...B-WH-90	G55 G56 G57
	120-005B		0.047	1.20	0.087	0.102	0.002		
	125-005B		0.049	1.25	0.087	0.102	0.002		
	145-010B		0.057	1.45	0.087	0.102	0.004		
	150-010B		0.059	1.50	0.087	0.102	0.004		
	200-010B		0.079	2.00	0.087	0.102	0.004		
	250-020B		0.098	2.50	0.087	0.102	0.008		
	300-020B		0.118	3.00	0.087	0.102	0.008		
 2-Edge Full-R 	GER 100-050AR	inch	0.039	1.00	0.059	0.071	0.020	SIGER...A-EH SIGER...A-WH	G55 G56
	200-100AR		0.079	2.00	0.059	0.071	0.039		
	GER 100-050BR		0.039	1.00	0.087	0.102	0.020	SIGER...B-EH SIGER...B-WH SIGER...B-WH-90	G55 G56 G57
	200-100BR		0.079	2.00	0.087	0.102	0.039		

- Dimension B : Available grooving depth

Recommended Cutting Conditions G58

Inserts are sold in 10 piece boxes.

kyocera@kyocera-tools.ru
www.kyocera-tools.ru

U.S. Stock Standard : ●
World Express (Shipping: 7-10 Business Days) : ○