

| SIZE / DESCRIPTION | GH# | Class of Fit | No. of Flutes | EDP Number Plug | Stock | EDP Number Bottom | Stock | Style Page 164 - 165 |
|--|-----|--------------|---------------|-----------------|-------|-------------------|-------|----------------------|
| 3/8"-24 NF | | | | | | | | |
| Recommended Hole Size based on 75% Thread = .3340" | | | | | | | | |
| L.H. SPIRAL POINT | 3 | 3B | 3 | 14194 | ◆ | - | - | See Page 164 (#2) |
| HAND TAP | 5 | - | 4 | 14195 | ◆ | 14196 | ◆ | See Page 164 (#1) |
| +.003 SPIRAL POINT | 7 | - | 3 | 14197 | ◆ | - | - | See Page 164 (#2) |
| +.005 HAND TAP | 11 | PLATING | 4 | 14198 | ◆ | 14199 | ◆ | See Page 164 (#1) |
| +.005 SPIRAL POINT | 11 | PLATING | 3 | 14200 | ◆ | - | - | See Page 164 (#2) |
| 6" EXT HAND TAP | 3 | 3B | 4 | 14201 | ◆ | 14202 | ◆ | See Page 164 (#4) |
| 3/8"-27 NS | | | | | | | | |
| Recommended Hole Size based on 75% Thread = .339" | | | | | | | | |
| HAND TAP | 3 | 3B | 4 | 14203 | ◆ | 14204 | ◆ | See Page 164 (#1) |
| 3/8"-32 NEF | | | | | | | | |
| Recommended Hole Size based on 75% Thread = .3447" | | | | | | | | |
| HAND TAP | 3 | 3B | 4 | 14205 | ◆ | 14206 | ◆ | See Page 164 (#1) |
| SPIRAL POINT | 3 | 3B | 3 | 14207 | ◆ | - | - | See Page 164 (#2) |
| HAND TAP | 5 | - | 4 | 14208 | ◆ | 14209 | ◆ | See Page 164 (#1) |
| 3/8"-40 NS | | | | | | | | |
| Recommended Hole Size based on 75% Thread = .3508" | | | | | | | | |
| HAND TAP | 2 | 3B | 4 | 14210 | ◆ | 14211 | ◆ | See Page 164 (#1) |
| 7/16"-24 NS | | | | | | | | |
| Recommended Hole Size based on 75% Thread = .3965" | | | | | | | | |
| HAND TAP | 3 | 3B | 4 | 14212 | ◆ | 14213 | ◆ | See Page 164 (#1) |
| HAND TAP | 5 | 2B | 4 | 14214 | ◆ | 14215 | ◆ | See Page 164 (#1) |
| 7/16"-32 NS | | | | | | | | |
| Recommended Hole Size based on 75% Thread = .4072" | | | | | | | | |
| HAND TAP | 3 | 3B | 4 | 14216 | ◆ | 14217 | ◆ | See Page 164 (#1) |
| 15/32"-32 NS | | | | | | | | |
| Recommended Hole Size based on 75% Thread = .4384" | | | | | | | | |
| HAND TAP | 3 | 3B | 6 | 14218 | ◆ | 14219 | ◆ | See Page 164 (#1) |
| 1/2"-10 ACME | | | | | | | | |
| Recommended Hole Size = .4000" | | | | | | | | |
| L.H. HAND TAP | - | 2G | 4 | 14220 | ◆ | - | - | See Page 165 (#12) |
| 1/2"-13 NC | | | | | | | | |
| Recommended Hole Size based on 75% Thread = .4251" | | | | | | | | |
| L.H. SPIRAL POINT | 3 | 3B | 3 | 14221 | ◆ | - | - | See Page 164 (#2) |
| +.005 HAND TAP | 11 | PLATING | 4 | 14222 | ◆ | 14223 | ◆ | See Page 164 (#1) |
| +.005 SPIRAL POINT | 11 | PLATING | 3 | 14224 | ◆ | - | - | See Page 164 (#2) |
| 6" EXT HAND TAP | 3 | 3B | 4 | 14225 | ◆ | 14226 | ◆ | See Page 164 (#4) |
| 6" EXT SPIRAL POINT | 3 | 3B | 3 | 14227 | ◆ | - | - | See Page 164 (#4) |

◆ : Usually Ships in 24-48 Hours
Depending on Size and Quantity

DRILLS
END MILLS
ROUTERS
THREAD MILLS & TAPS
ENGRAVERS
BORING BARS
REAMERS
SAWS
TECHNICAL
INDEX