




Product Lineup

Dynamic Bar

Application	Overview Shape	Boring Bar Type	Shank Type Max. Overhang Length (L/D)	Coolant Hole		Min. Bore Dia. ØA																						Refer Page for Toolholder
				Yes	No	5	6	7	8	10	12	13	14	16	18	20	22	23	25	26	27	30	31	32	34	40	50	
Boring / Internal Facing		A...SCLC-AE	Excellent L/D = ~5.5	●						●	●		●		●		●				●							F24
		S...SCLC-AE	Excellent L/D = ~5.5	○		●	●	●	●																			
		S...SCLC-A	Steel L/D = ~4	○						●	●		●		●		●				●							
		C...SCLC-A	Carbide L/D = ~7	○		●	●	●	●																			
		E...SCLC-A	Carbide L/D = ~7	●						●	●		●		●		●				●							F26
		A...SCLP-AE	Excellent L/D = ~5.5	●						●			●	●	●		●				●							
		S...SCLP-A	Steel L/D = ~4	○						●			●	●	●		●				●							
		E...SCLP-A	Carbide L/D = ~7	●						●			●	●	●		●				●							
		E...STLP-A	Carbide	●					●	●	●		●		●		●				●							F32
		C...STLB-A	L/D = ~7	○					●																			
		A...STLP-AE	Excellent	●						●	●		●		●		●				●							
		S...STLB-AE	L/D = ~5.5	○					●																			
		S...STLB(P)-A	Steel L/D = ~4	○					●	●	●		●		●		●				●							F34
		A...STLC-AE	Excellent L/D = ~5.5	●						●	●		●		●		●											
		S...STLC-A	Steel L/D = ~4	○						●	●		●		●		●											F40
Boring		S...SWUB(P)-A	Steel L/D = ~4	○		●	●	●	●	●			●	●	●	●	●											
		S...SWUB-AE	Excellent L/D = ~5.5	○		●	●	●	●																			
		A...SWUB(P)-AE	Excellent L/D = ~5.5	●						●			●	●	●	●	●											
		C...SWUB-A	Carbide L/D = ~7	○		●	●	●																				
		E...SWUB(P)-A	Carbide L/D = ~7	●						●	●		●		●	●	●											