

● Applicable Sleeve

(Tip-Bar installation side) Fig.1		(Tip-Bar installation side) Fig.2		(Tip-Bar installation side) Fig.3																			
Description	Std.	Dimension (mm)								Drawing	Spare Parts		Applicable Machine Manufacturer	Ref. Page for 2-Edge Tip-Bar (Ref. Page for other 2-Edge Tip-Bar)									
		*ød1	øD1	øD2	ød2	H	L1	L2	L3		Screw	Wrench											
PSH 0412-80	●	4	12	16	6	11	80	20	-	Fig.1	HS4×4P	LW-2	(General use)										
0512-80	●	5			8																		
0612-80	●	6																					
0712-80	●	7																					
PSH 0416-100	●	4	16	-	6	15	100	-	-	Fig.2	HS4×4P	LW-2											
0516-100	●	5			8																		
0616-100	●	6																					
0716-100	●	7																					
PSH 0420-120	●	4	20	17.5	6	19	120	20	9	Fig.3	HS4×4P	LW-2	Amada Wasino Eguro Citizen machinery Precision Tsugami Miyano (General use)										
0520-120	●	5			8				7.5														
0620-120	●	6																					
0720-120	●	7																					
PSH 0425.0-135	●	4	25	18	6	24	135	23	9.5	Fig.3	HS4×4P	LW-2	Amada Wasino Eguro Precision Tsugami Miyano (General use)										
0525.0-135	●	5			8				8														
0625.0-135	●	6																					
0725.0-135	●	7																					
PSH 0419-120	●	4	19.05 (0.75")	17.5	6	18	120	20	9	Fig.3	HS4×4P	LW-2	Citizen Machinery										
0519-120	●	5			8				7.5														
0619-120	●	6																					
0719-120	●	7																					
PSH 0425-120	●	4	25.4 (1")	18	6	24.4	120	23	9.5	Fig.3	HS4×4P	LW-2											
0525-120	●	5			8				8														
0625-120	●	6																					
0725-120	●	7																					
PSH 0422-135	●	4	22	18	6	21	135	22	9.5	Fig.3	HS4×4P	LW-2	Star Micronics Nomura VTC										
0522-135	●	5			8				8														
0622-135	●	6																					
0722-135	●	7																					
PSH 0423-120	●	4	23	18	6	22	120	22	9.5	Fig.3	HS4×4P	LW-2	Nomura VTC										
0523-120	●	5			8				8														
0623-120	●	6																					
0723-120	●	7																					

Grooving
(HPG)
⇒ G30

Boring
(HPB) ⇒ F18

Back Boring
(HPBT) ⇒ F18

Face Grooving
(HPFG) ⇒ G53

Threading
(HPT) ⇒ J24

*: Length of øD1...20mm (PSH04)

...25mm (PSH05, PSH06, PSH07)

• Choose sleeves (øD1) to meet with øD dimension of Tip-Bar.

• Names of machine builders are listed in the order of the Japanese syllabary with omitted titles of respect.



Grooving
(HPG) ⇒ G30

Boring
(HPB) ⇒ F18

Back Boring
(HPBT) ⇒ F18

Face Grooving
(HPFG) ⇒ G53

Threading
(HPT) ⇒ J24