

GMG / GMM / GMGA 8030 (Face Grooving)

Workpiece Material	Recommended Insert Grade (Cutting Speed: m/min)						Face Grooving			Traversing			Remarks
	Cermet	CVD Coated Carbide	PVD Coated Carbide		Carbide		Width (mm)			Width (mm)			
	TN90	CR9025	PR915	PR930	PR905	KW10	8.0			8.0			
							f (mm/rev)			f (mm/rev)			
Carbon Steel	☆ 100~220	☆ 80~160	☆ 80~160	★ 80~160	-	-	0.1~0.2			0.1~0.25			Coolant
Alloy Steel	☆ 80~160	☆ 70~160	☆ 70~160	★ 70~160	-	-	0.1~0.2			0.1~0.25			
Stainless Steel	☆ 70~140	☆ 60~130	★ 60~130	☆ 60~130	-	-	0.1~0.2			0.1~0.25			
Cast Iron	-	-	-	-	★ 80~180	☆ 70~130	0.1~0.3			0.1~0.35			
Aluminum	-	-	-	-	-	★ 200~300	0.08~0.25			0.08~0.30			
Brass	-	-	-	-	-	★ 100~150	0.08~0.25			0.08~0.30			

★ : 1st Recommendation ☆ : 2nd Recommendation

FMM • FMN

Workpiece Material	Recommended Insert Grade (Cutting Speed: m/min)						Face Grooving (FMM type / FMN type)			Traversing (Case of FMM type)			Remarks
	Cermet	CVD Coated Carbide	PVD Coated Carbide		Carbide		Width (mm)			Width (mm)			
	TN90	CR9025	PR915	PR930	PR905	KW10	3.0	4.0	5.0 / 6.0	3.0	4.0	5.0 / 6.0	
							f (mm/rev)			f (mm/rev)			
Carbon Steel	☆ 100~220	☆ 80~200	☆ 80~200	★ 80~200	-	-	0.03~0.05	0.03~0.08	0.05~0.10	0.05~0.10	0.05~0.25	0.10~0.30	Coolant
Alloy Steel	☆ 80~200	☆ 70~180	☆ 70~180	★ 70~180	-	-	0.03~0.05	0.03~0.08	0.05~0.10	0.05~0.10	0.05~0.25	0.10~0.30	
Stainless Steel	☆ 70~160	☆ 60~150	★ 60~150	☆ 60~150	-	-	0.03~0.05	0.03~0.08	0.05~0.10	0.05~0.10	0.05~0.25	0.10~0.30	
Cast Iron	-	-	-	-	★ 80~180	☆ 70~150	0.03~0.05	0.03~0.08	0.05~0.10	0.05~0.10	0.05~0.25	0.10~0.30	
Aluminum	-	-	-	-	-	★ 200~500	0.03~0.05	0.03~0.08	0.05~0.10	0.05~0.10	0.05~0.25	0.10~0.30	
Brass	-	-	-	-	-	★ 100~200	0.03~0.05	0.03~0.08	0.05~0.10	0.05~0.10	0.05~0.25	0.10~0.30	

Set the feed rate 1/100 of edge width on the first groove and check chip evacuation.

★ : 1st Recommendation ☆ : 2nd Recommendation

FMN type Inserts are only for Deep Grooving, and when used for traversing, set to ap=0.2mm and under.

◆ See the notes below for traversing conditions.

ap and f of FMM

	Recommended Conditions
ap (MAX) mm	under 50% of Edge Width
f (MAX) mm/rev	under 3~5% of Edge Width

· $ap \leq 0.5w$

· $f \leq [0.03 \text{ (Min.)} \sim 0.05 \text{ (MAX.)}] w$

ap×f should be as follows.

Load (mm ²) \ Edge Width (mm)	3.0	4.0	5.0	6.0
ap×f	~0.09	~0.14	~0.25	~0.36

· $ap \times f \leq 0.01 w^2$

G



Grooving