

Turning Indexable Inserts

55°Parallelogram • Negative without Hole

(mm)

Description	A	T	ød
KNMX1604_	9.525	4.76	-

B




Negative



Insert (Turning)

Insert	Description	Dim. (mm)	Material														Carbide	Ref. Page for Toolholder	Applicable Chipbreaker Range							
			Cermet	PVD Cermet		CVD Coated Carbide						PVD Coated Carbide			Carbide											
rε			TN6010	TN6020	TN60	PV7005	PV7010	PV7020	CA5505	CA5515	CA5525	CA5535	CA6515	CA6525	CA4010	CA4115	CA4120	CA4505	CA4515	PR930	PR1005	PR1025	PR1125	KW10		
KNMX 160405%L-1 160410%L-1		0.5 1.0								●	●															
Medium-Roughing																										



Round • Negative with Hole


(mm)

(mm)

Description	A	T	ød
RN_0903_	9.525	3.96	3.81
RN_1204_	12.70	4.76	5.16

Description	A	T	ød
RN_1506_	15.875	6.35	6.35

Insert	Description	Dim. (mm)	Material														Carbide	Ref. Page for Toolholder	Applicable Chipbreaker Range							
			Cermet	PVD Cermet		CVD Coated Carbide						PVD Coated Carbide			Carbide											
rε			TN6010	TN6020	TN60	PV7005	PV7010	PV7020	CA5505	CA5515	CA5525	CA5535	CA6515	CA6525	CA4010	CA4115	CA4120	CA4505	CA4515	PR930	PR1005	PR1025	PR1125	KW10		
RNMG 090300		-				●	●			●	●															
RNMG 120400		-				●	●			●	●					●	●									
RNMG 150600		-								●	●					●	●									
Medium-Roughing																										



Inserts are sold in 10 piece boxes.