












Milling Indexable Inserts

Milling Inserts (with Hole)

[illegible]

Insert		Description	Dimension (mm)				Angle (°)				Material										Ref. Pac			
			A	T	ød	X	Z	α	β	γ	Cermets	PVD Coated				Carbide								
Handed Insert shows Right-hand												TN100M	TC60	PR630	PR730	PR830	PR1230	PR1210	PR1025	PR660	PR905	PW30	KW10	
		SEMM 09T308PESR	9.525	3.97	3.4	-	rε=0.8	20°	-	-	●	●	●							●	●		●	M42
		150408PESR	15.875	4.76	5.5						●	●	●						●	●		●	M43	
		SOMT 0903AXEN-J	9.525	3.18	3.4	0.5	1.1	27°	32°	45°	●	●	●							●	●		●	M34
		SOMW 0903AXTN 0903AXFN	9.525	3.18	3.4	0.5	1.1	27°	32°	45°	●	●	●							●	●		●	
 2-Notched		SPMT 1806EDER-NB2	18	6.35	6.8	R1.2	3.1	11°	15°	15°				●	○		○			●	●			M35
 3-Notched		SPMT 1806EDER-NB3	18	6.35	6.8	R1.2	3.1	11°	15°	15°				●	○		○			●	●			
 Tough Edge 2-Notched		SPMT 1806EDSR-NB2T	18	6.35	6.8	R1.2	3.1	11°	15°	15°				●	○		○			●				-
		SPMT 1806EDSL-NB2T												●										
 Tough Edge 3-Notched		SPMT 1806EDSR-NB3T	18	6.35	6.8	R1.2	3.1	11°	15°	15°				●	○		○			●				M35
		SPMT 1806EDSL-NB3T												●										
 Low resistance type 4-Notched		SPMT 1806EDER-NB2P	18	6.35	6.8	R1.2	3.1	11°	15°	15°				●	○		○			●				M35
 Low resistance type 5-Notched		SPMT 1806EDER-NB3P	18	6.35	6.8	R1.2	3.1	11°	15°	15°				●	○		○			●				
 Without Notch		SPMT 1806EDER-V	18	6.35	6.8	R1.2	3.1	11°	15°	15°				●	○		○			●	●			

Inserts are sold
in 10 piece boxes.

● : Std. Item ○ : Check Availability R : Std. Item (R-hand Only) L : Std. Item (L-hand Only)

kyocera@kyocera-tools.ru
www.kyocera-tools.ru