






Screws

Shape	Description		Dimension (mm)						Angle (°)		Remarks		
			A	B	C	D	E	F	α	θ			
	LS	-1	M6X1.0	17.0	6.0	-	2.5	2.5	-	-	With N is silver plated		
-1N													
-1S													
-1SN													
-1T		21.0											
-2		M8X1.0	20.0	8.0	-	3.0	3.0	-	-				
-2N			22.0										
-3													
-4	24.0												
-4N													
	LS	-11	M6X1.0	9.5	-	-	3.0	-	-	-			
-15		12.5											
	M	3X8	M3X0.5	8.0	5.5	2.0	-	-	-	-	Flat fillister head screw equivalent to JIS B-1101		
3X12		12.0											
4X10		M4X0.7	10.0	7.0	2.6								
	SB	-1TR	M2X0.4	5.3	3.8	-	-	T6	-	82°	R...shows Right-hand Thread		
		-2TR	M2.5X0.45	6.2	4.5			T8					
		-3TR	M3X0.5	7.2	4.8			T10					
		-3STR		6.4	5.2								
		-3.5TR	M3.5X0.6	9.3	5.6			T15					
		-4TR	M4X0.7	7.7	5.8								
		-5TR	M5X0.8	20.0	8.7			T20					
		-2290TR	M2.2X0.45	9.2	2.8			T6		90°			
		-25100TR	M2.5X0.45	10.0	3.5			T7					
		-40115TR	M4X0.7	11.5	5.5			T15				60°	
		-5070TR	M5X0.8	7.0	6.8			T20					
		-5090TR		9.0									
		-50120TR		12.0									
	SB	-1635TR	M1.6X0.35	3.3	2.6	-	-	T6	-	60°	R...shows Right-hand Thread		
	SB	-1STR	M2X0.4	5.0	3.1								
		-2035TR		3.7	3.0								
		-2035TRG		3.5	2.7								
		-2040TR		3.8	3.0								
		-2040TRG		4.0	3.0								
		-2042TRG		4.1	2.7								
		-2045TR		4.3	2.7								
		-2045TRN		4.3	2.8					37°			
		-2050TR		4.8	3.0					60°			
		-2060TR		5.8	3.5								
	SB	-2080TR	M2.2X0.45	8.3	2.8			T8	-	60°			
		-2250TR		5.1	3.1								
		-2255TR		5.5	3.5								
		-2260TR		5.8	3.1								
	SB	-2545TR	M2.5X0.45	4.6	3.5			T8	-	60°			
		-2555TRG		5.4									
		-2560TR		5.7									
		-2570TR		6.8									
	SB	-3060TR	M3X0.5	5.3	4.2			T10	-	60°			
		-3060TRG		5.9									
		-3070TRG		7.0									
		-3080TR		8.0									

• For tightening torque of Torx screw, see P6.