







Screws

Shape	Description	Dimension (mm)						Angle (°)		Remarks
		A	B	C	D	E	F	α	θ	
	SV -60136R	M6X1.0	13.6	6.3	-	4	-	-	6°	Hexagon socket
	-60136TR					-	T20	-		Torx
	TH 8X15	M8X1.25	20.0	8.5	-	4.0	-	-	-	
	W 8X18	M8X1.25	18.0	-	-	4.0	-	-	-	
	8X21	M8X1.0	21.0							
	W 6X17	M6X1	17.0	-	-	-	T20	-	-	
	8X16	M8X1	16.0				T25			
	HH 8X25H	M8X1.25	25.0	13.0	8.0	5.0	-	-	-	With Coolant Hole
	10X30H	M10X1.5	30.0	16.0	10.0	6.0				
	12X35H	M12X1.75	35.0	18.0	12.0	8.0				
	16X52H	M16X2.0	36.0	24.0	16.0	12.0				
	HF 20X53H	M20X2.5	35.0	43.0	18.0	14.0	14.0	-	-	With Coolant Hole
	24X60H	M24X3.0	40.5	65.0	19.5	17.0	14.0			

Tightening Torque

Torx Size	Tightening Torque (N/m)
T6	0.5
T7	0.8
T8	1.0
T10	2.0
T15	3.5
T20	5.0
T25	7.5

Reference

Torx and Torx Plus have different cross-section.



Torx



Torx Plus