







# Wrenches / Spanners

| Shape                                                                               | Description     | Dimension (mm) |      |      |     |      |      | Angle (°) |          | Remarks                   |
|-------------------------------------------------------------------------------------|-----------------|----------------|------|------|-----|------|------|-----------|----------|---------------------------|
|                                                                                     |                 | A              | B    | C    | D   | E    | F    | $\alpha$  | $\theta$ |                           |
|    | <b>DT -7</b>    | 44             | 16   | -    | 114 | -    | T7   | -         | -        | Torx                      |
|                                                                                     | <b>-8</b>       | 70             | 26   | -    | 150 | -    | T8   | -         | -        |                           |
|    | <b>DT -10</b>   | 70             | 29   | -    | 160 | -    | T10  | -         | -        | Torx                      |
|                                                                                     | <b>-15</b>      | 70             | 32   | -    | 170 | -    | T15  | -         | -        |                           |
|                                                                                     | <b>-20</b>      | 90             | 32   | -    | 190 | -    | T20  | -         | -        |                           |
|                                                                                     | <b>-25</b>      | 82             | 36   | -    | 190 | -    | T25  | -         | -        |                           |
|    | <b>DTM -6</b>   | 39             | 17   | -    | 113 | -    | T6   | -         | -        | Top of Torx is magnetized |
|                                                                                     | <b>-8</b>       | 70             | 24   | -    | 150 | -    | T8   | -         | -        |                           |
|                                                                                     | <b>-15</b>      | 70             | 31   | -    | 174 | -    | T15  | -         | -        |                           |
|                                                                                     | <b>DTP -15</b>  | 81             | 33   | -    | 186 | -    | 15IP | -         | -        | Torx Plus                 |
|                                                                                     | <b>-20</b>      | 100            |      |      | 206 |      | 20IP |           |          |                           |
|    | <b>FH -2</b>    | 42             | 20   | -    | 73  | 2.0  | -    | -         | -        | Hexagon                   |
|                                                                                     | <b>-2.5</b>     | 42             | 20   | -    | 73  | 2.5  | -    | -         | -        |                           |
|  | <b>FT -6</b>    | 30             | 20   | -    | 65  | -    | T6   | -         | -        | Torx                      |
|                                                                                     | <b>-7</b>       | 34             | 15   | -    | 62  | -    | T7   | -         | -        |                           |
|                                                                                     | <b>-8</b>       | 35             | 20   | -    | 74  | -    | T8   | -         | -        |                           |
|                                                                                     | <b>-10</b>      | 40             | 20   | -    | 74  | -    | T10  | -         | -        |                           |
|  | <b>FT -15</b>   | 43             | 25.0 | 10.0 | 80  | -    | T15  | -         | -        | Torx                      |
|  | <b>LTW -8SS</b> | 45             | 6.0  | -    | -   | -    | T8   | -         | -        | Torx                      |
|                                                                                     | <b>-10S</b>     | 65             | 10.0 | -    | -   | -    | T10  | -         | -        |                           |
|                                                                                     | <b>-10SS</b>    | 50             | 7.0  | -    | -   | -    | T10  | -         | -        |                           |
|                                                                                     | <b>-15S</b>     | 65             | 10.0 | -    | -   | -    | T15  | -         | -        |                           |
|                                                                                     | <b>-20</b>      | 57             | 20.0 | -    | -   | -    | T20  | -         | -        |                           |
|  | <b>LW -1.5</b>  | 45             | 14   | -    | -   | 1.5  | -    | -         | -        | Hexagon                   |
|                                                                                     | <b>-2</b>       | 50             | 16   | -    | -   | 2.0  | -    | -         | -        |                           |
|                                                                                     | <b>-2.5</b>     | 56             | 18   | -    | -   | 2.5  | -    | -         | -        |                           |
|                                                                                     | <b>-3</b>       | 63             | 20   | -    | -   | 3.0  | -    | -         | -        |                           |
|                                                                                     | <b>-4</b>       | 70             | 25   | -    | -   | 4.0  | -    | -         | -        |                           |
|                                                                                     | <b>-4.5</b>     | 78             | 26   | -    | -   | 4.5  | -    | -         | -        |                           |
|                                                                                     | <b>-5</b>       | 80             | 28   | -    | -   | 5.0  | -    | -         | -        |                           |
|                                                                                     | <b>-6</b>       | 90             | 32   | -    | -   | 6.0  | -    | -         | -        |                           |
|                                                                                     | <b>-8</b>       | 109            | 36   | -    | -   | 8.0  | -    | -         | -        |                           |
|                                                                                     | <b>-10</b>      | 112            | 40   | -    | -   | 10.0 | -    | -         | -        |                           |
|                                                                                     | <b>-14</b>      | 140            | 56   | -    | -   | 14.0 | -    | -         | -        |                           |
|                                                                                     | <b>-17</b>      | 160            | 63   | -    | -   | 17.0 | -    | -         | -        |                           |
|                                                                                     | <b>-19</b>      | 180            | 70   | -    | -   | 19.0 | -    | -         | -        |                           |

P



Spare Parts

## Reference

L-shape type (LTP-10, LTP-15: described in **F42** and **F43**) is Torx Plus.  
Screwdriver type DTP-9 (described in **M116** and **M117**) is also Torx Plus.