

Dynamic Bar [WB , WP Insert]

S / A-SWUB(P)-AE Excellent Bar (Boring)

Max. Overhang Length L/D=~-5.5

Fig.1

Fig.2

0° for A08X-SWUB%.08-10AE, A10L-SWUB%.08-12AE

Shank Dia. øD	Straight hole Dia. ød
ø8	ø2.5
ø10	ø3
ø12	ø4
ø16	ø5
ø20	ø5

• Right-hand shown

L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder.

S-SWUB(P)-A Steel Bar (Boring)

Max. Overhang Length L/D=~-4

Fig.3

Fig.4

0° for S08X-SWUB%.08-10A, S10L-SWUB%.08-12A

• Right-hand shown

L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder.

E(C)-SWUB(P)-A Carbide Shank Bar (Boring)

Max. Overhang Length L/D=~-7

Fig.5

Fig.6

0° for E08L-SWUB%.08-10A, E10N-SWUB%.08-12A, E10N-SWUB%.08-12A-2/3, E10N-SWUB%.08-12A-1/2

Shank Dia. øD	Straight hole Dia. ød
ø5	-
ø6	-
ø7	-
ø8	ø3
ø10	ø3
ø12	ø4
ø16	ø4
ø20	ø6

• Right-hand shown

L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder.

F

Boring