

General Purpose Face Grooving $\phi 20\sim$

Type	KFTB
Min. Face Groove Dia.	$\phi 65\sim\phi 250$
Width (mm)	4.0~5.0
Grooving Depth (mm)	25~38
Ref. Page	G87

Type	GFV
Min. Face Groove Dia.	$\phi 20\sim\phi 150$
Width (mm)	2.0~6.0
Grooving Depth (mm)	2.2~8.1
Ref. Page	G78

Type	GFVS
Min. Face Groove Dia.	$\phi 35\sim\phi 150$
Width (mm)	2.5~6.0
Grooving Depth (mm)	4.6~8.1
Ref. Page	G80

Type	GFVT
Min. Face Groove Dia.	$\phi 35\sim\phi 150$
Width (mm)	2.5~6.0
Grooving Depth (mm)	4.6~8.1
Ref. Page	G80

Face Grooving & Longitudinal turning $\phi 25\sim$ (CERACUT Plunge & Turn)

Type	KFMS
Min. Face Groove Dia.	$\phi 25\sim\phi 235$
Width (mm)	3.0~6.0
Grooving Depth (mm)	13~32
Ref. Page	G84

Type	KFMS-8
Min. Face Groove Dia.	$\phi 54\sim\phi 155$
Width (mm)	8.0
Grooving Depth (mm)	25
Ref. Page	G86

Face Grooving $\phi 35\sim$

Type	GIFV
Min. Face Groove Dia.	$\phi 35\sim\phi 50$
Width (mm)	2.0~6.0
Grooving Depth (mm)	2.2~8.1
Ref. Page	G88