

## General Purpose Face Grooving $\phi 20\sim$

Type	<b>KFTB</b>
Min. Face Groove Dia.	$\phi 65\sim\phi 250$
Width (mm)	4.0~5.0
Grooving Depth (mm)	25~38
Ref. Page	<b>G87</b>

Type	<b>GFV</b>
Min. Face Groove Dia.	$\phi 20\sim\phi 150$
Width (mm)	2.0~6.0
Grooving Depth (mm)	2.2~8.1
Ref. Page	<b>G78</b>

Type	<b>GFVS</b>
Min. Face Groove Dia.	$\phi 35\sim\phi 150$
Width (mm)	2.5~6.0
Grooving Depth (mm)	4.6~8.1
Ref. Page	<b>G80</b>

Type	<b>GFVT</b>
Min. Face Groove Dia.	$\phi 35\sim\phi 150$
Width (mm)	2.5~6.0
Grooving Depth (mm)	4.6~8.1
Ref. Page	<b>G80</b>

## Face Grooving & Longitudinal turning $\phi 25\sim$ (CERACUT Plunge & Turn)

Type	<b>KFMS</b>
Min. Face Groove Dia.	$\phi 25\sim\phi 235$
Width (mm)	3.0~6.0
Grooving Depth (mm)	13~32
Ref. Page	<b>G84</b>

Type	<b>KFMS-8</b>
Min. Face Groove Dia.	$\phi 54\sim\phi 155$
Width (mm)	8.0
Grooving Depth (mm)	25
Ref. Page	<b>G86</b>

## Face Grooving $\phi 35\sim$

Type	<b>GIFV</b>
Min. Face Groove Dia.	$\phi 35\sim\phi 50$
Width (mm)	2.0~6.0
Grooving Depth (mm)	2.2~8.1
Ref. Page	<b>G88</b>